

MOBI TECH MB-SPH2406K1S
24+2+1 Port 400W POE Switch



- ✧ 24*10/100Mbps POE port;2*10/100/1000Mbps UP Link;
1*10/100/1000Mbps SFP
- ✧ 250m Distance,VLAN ,AI watchdog
- ✧ Support IEEE802.3AF/AT
- ✧ Whole Power:400W(52V 7.7A)
- ✧ All port supported by MDI/MDIX auto flip and self negotiation
- ✧ Supply 28*10/100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- ✧ Support IEEE802.3x flow control for Full-duplex mode and back pressure for Half-duplex mode.
- ✧ Each port max. power supply reached 30W.

Application:

- ✧ Wireless Access Point
- ✧ IP Camera
- ✧ IP Phone
- ✧ Computer Networks

Model	24+2+1 port 400W POE switch(Built-in)
Model No.	MB-SPH2406K1S
PoE Port	1 to 24 port support 100Mbps IEEE802.3af/at
UP link port	25 th -27 th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE type	End-span
Power/Data distance	≤250m
Network Standard	IEEE 802.3、 IEEE802.3u、 802.3x、 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Switch capability	12.8Gbps
Forwarding Mode	Store and forward
Forwarding Method	10BASE-tx:14880pps/port 100BASE-tx:148800pps/port 1000BASE-tx:1488000pps/port
Forwarding Rate	9.52Mpps
MAC Address	8K MAC address table
Port function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps;POE Status indicator; POWER indicator
Working Environment	Working Temperature: -10°-- 55°C Storage temperature: -40°-- 85°C
Input power	AC100-240V 50/60HZ
Weight&Size	2.1kg 270mm*181mm*44mm(L*W*H)